

Specifications

| SECTION SUBJECT | GL1500'90 | GL1500SE'90 |
|----------------------------------|--------------------------|--------------------------|
| ENGINE | | |
| Cylinder | 6 cylinder | 6 cylinder |
| Strokes | 4-Stroke | 4-Stroke |
| Cooling | Water Cooled | Water Cooled |
| Camshaft | OHC | OHC |
| Valves per cylinder | 2 | 2 |
| Displacement | 1520cc | 1520cc |
| Lubrication system | Wet Sump | Wet Sump |
| Carburetor | 36mm(2) | 36mm(2) |
| Main jet | = 90 = 158 | = 90 = 158 |
| Slow jet | = 60 | = 60 |
| TRANSMISSION | | |
| Transmission type | Constant Mesh | Constant Mesh |
| Transmission speeds | 5-Speed | 5-Speed |
| Clutch | Wet Multi-Plate | Wet Multi-Plate |
| Shift pattern | 1-N-2-3-4-OD | 1-N-2-3-4-OD |
| CHASSIS | | |
| Fuel tank capacity (Std) | 6.3gal | 6.3gal |
| Fuel tank capacity (Res) | 1.1gal | 1.1gal |
| Air filter type | Paper | Paper |
| Front Brake | Double Disc | Double Disc |
| Rear Brake | Single Disc | Single Disc |
| Front tire | 130 70-18 63R | 130 70-18 63H |
| Tire pressure | 33PSI | 33PSI |
| Rear tire | 160 80-16 75H | 160 80-16 75H |
| Tire pressure | 41PSI | 41PSI |
| SERVICE/TUNING | | |
| Ignition type | Full Transistor | Full Transistor |
| Spark plug gap | 0.8-0.9mm (0.031-0.035") | 0.8-0.9mm (0.031-0.035") |
| LUBRICATION | | |
| Recommended fuel | 86 + Octane | 86 + Octane |
| Engine oil - Pro Honda | | |
| GN4 10W40 | 08C35-A14'M01 | 08C35-A14'M01 |
| GN4 20W50 | 08C35-A25'M01 | 08C35-A25'M01 |
| Engine oil capacity: | | |
| After draining | 3.9qt | 3.9qt |
| After reassembly | 4.5qt | 4.5qt |
| Coolant type | 08C50-C32'S01 | 08C50-C32'S01 |
| Coolant ratio | 50:50 | 50:50 |
| Capacity | 4.3qt | 4.3qt |
| Drive shaft and final gear case: | | |
| Pro Honda shaft drive oil | 08208-0080 | 08208-0080 |
| Fork oil: | | |
| Pro Honda (5W SS-7) | 08208-0005 | 08208-0005 |
| Pro Honda (10W SS-8) | 08208-0010 | 08208-0010 |