





ENGINE	
Engine Type	670cc liquid-cooled parallel-twin
Bore And Stroke	73mm x 80mm
Induction	PGM-FI, 36mm throttle body
Ignition	Digital transistorized with electronic advance
Compression Ratio	10.7:1

Valve Train SOHC; four valves per cylinder

**DRIVE TRAIN** 

Transmission Automatic six-speed with two automatic modes and a manual mode

Final Drive Chain

CHASSIS / SUSPENSION / BRAKES

Front Suspension 43mm fork; 3.9 inches travel

Rear Suspension Pro-Link® single shock; 3.9 inches travel

Front Brake Single 320mm disc with two-piston caliper with ABS

Rear Brake Single 240mm disc with single-piston caliper with ABS

Front Tire 120/70ZR18 radial Rear Tire 200/50ZR17 radial

DIMENSIONS

Rake 27.0 degrees

Trail 110.0mm (4.3 inches)

Wheelbase 64.8 inches
Seat Height 25.6 inches

Curb Weight 562 pounds. Includes all standard equipment, required fluids and full tank of

fuel-ready to ride

Fuel Capacity 3.06 gallons Mpg 61 MPG\*

**OTHER** 

Note

Model Id NC700JD

Emissions Meets current EPA standards. Models sold in California meet current CARB

standards and may differ slightly due to emissions equipment.

Available Colors Matte Black Metallic

\*Honda's fuel economy estimates are based on EPA exhaust emission

measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle,

weather, road conditions, tire pressure, installation of accessories, cargo, rider and

passenger weight, and other factors.

**FACTORY WARRANTY INFORMATION** 

One Year Transferable, Unlimited-mileage limited warranty; extended coverage available with

a Honda Protection Plan.