



2015 INTERCEPTOR DLX SPECIFICATIONS*

ENGINE

Engine Type	782cc liquid-cooled 90° V-4
Bore And Stroke	72mm x 48mm
Induction	PGM-FI Programmed automatic enrichment circuit, with 36mm throttle bodies
Ignition	Digital transistorized with electronic advance
Compression Ratio	11.8:1
Valve Train	VTEC DOHC; four valves per cylinder

DRIVE TRAIN

Transmission	Close-ratio six-speed
Final Drive	#525 O-ring chain

CHASSIS / SUSPENSION / BRAKES

Front Suspension	43mm with spring-preload adjustability; 4.3 inches travel
Rear Suspension	Pro Arm single-side swingarm with Pro-Link® single spring-preload and rebound damping adjustability; 4.7 inches travel
Front Brake	Dual radial mount four-piston calipers with full-floating 310 mm discs; ABS
Rear Brake	Single 256mm disc; ABS
Front Tire	120/70ZR-17 radial
Rear Tire	180/55ZR-17 radial

DIMENSIONS

Rake	25.5°
Trail	95mm (3.74 inches)
Wheelbase	57.4 inches
Seat Height	31 inches to 31.8 inches
Curb Weight	536 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	5.2 gallons

OTHER

Emissions	Meets current EPA standards. California version meets current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Red, Pearl White
Model Id	VFR800FD

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan
----------	--