

## TIRES

The ATC185S is equipped with 22x11.0-8 low pressure tubeless tires to promote comfortable riding. Although the tires are designed specifically for vigorous off-road use, they are not immune to punctures. Always select your riding area with care.

### CAUTION:

\* *Driving on paved surfaces will cause excessive tire wear.*

For normal use, the tires should be inflated to a recommended pressure of 2.2 psi (15 kpa, 0.15 kg/cm<sup>2</sup>). A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

### NOTE:

\* Tire pressure should be checked when the tires are "cold", before you ride.

If no air pressure gauge is available to accurately measure 2.2 psi (15 kpa, 0.15 kg/cm<sup>2</sup>), this value can be estimated by measuring the circumference of the tires with a measuring tape. When inflated to 2.2 psi (15 kpa, 0.15 kg/cm<sup>2</sup>), the maximum tire circumference measured over the tread ribs will be approximately 1,743 mm (68.6 in.). The relationship

between tire pressure and actual circumference varies slightly with factors of wear and stretching that occur through use.

Recommended Pressure: 2.2 psi (15 kpa, 0.15 kg/cm<sup>2</sup>)

Standard Tire Circumference: 1,743 mm (68.6 in.)

Min. Pressure: 1.7 psi (12 kpa, 0.12 kg/cm<sup>2</sup>)

