

## LOADING AND ACCESSORIES

 **WARNING**

*\* To prevent an accident, use extreme care when adding and riding with accessories and cargo. Addition of accessories and cargo can reduce the ATC 200E stability, performance, and safe operating speed. Slow down (15 mph or less) when loaded with cargo or pulling a trailer.*

The combined weight of the rider, cargo and all accessories must not exceed **150 kg (330 lbs)** which is the vehicle capacity load.

Loading capacity data given below are mutually exclusive, and are valid only where the ground is level and flat.

For varied loading conditions and terrains, you must exercise your own judgement in selecting the vehicle speed and maneuver.

1. Load cargo on the rear carrier as far forward as possible. Do not allow cargo to extend beyond the end of the rear carrier.

**Front carrier**     **10 kg (22 lbs.)**  
**Rear carrier**     **45 kg (100 lbs.)**

2. When towing a trailer, care should be taken to maintain balance and stability. Place cargo in the trailer so that it will not cause the front wheel to lift off the ground during travel.

**Trailer gross weight**                     **315 kg (700 lbs.)**

**(Trailer plus cargo weight)**

**Weight on hitch point**                     **14 kg (30 lbs.)**

3. Do not obstruct the headlight beam with cargo.

4. Do not ride with a passenger on the rear carrier.

This ATC was not designed to carry passengers.