



Specifications

■ Service Data

Tyre size	Front	120/60ZR17M/C (55W)
	Rear	160/60ZR17M/C (69W)
Tyre type	Radial, tubeless	
Recommended Tyres	Front	DUNLOP D204FL BRIDGESTONE BT-50F
	Rear	DUNLOP D204J BRIDGESTONE BT-50R
Tyre air pressure (Driver only)	Front	225 kPa (2.25 kgf/cm ² , 33 psi)
	Rear	250 kPa (2.50 kgf/cm ² , 36 psi)
Tyre air pressure (Driver and passenger)	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
	Rear	290 kPa (2.90 kgf/cm ² , 42 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	(standard)	CR8EH-9 (NGK) or U24FER9 (DENSO)
Spark plug gap	0.80 to 0.90 mm (0.031 to 0.035 in)	
Idle speed	1,400 ± 100 rpm	

Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving," SAE 10W-30, JASO T 903 standard MA	
Engine oil capacity	After draining	3.0 litres (3.2 US qt, 2.6 Imp qt)
	After draining & engine oil filter change	3.2 litres (3.4 US qt, 2.8 Imp qt)
	After disassembly	3.8 litres (4.0 US qt, 3.3 Imp qt)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	2.2 litres (2.3 US qt, 1.9 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	

Specifications