

● Tire Information

Correct air pressure will provide maximum safety, stability, riding comfort and tire life.

Be sure to follow the tire specification.

Cold tire pressures psi (kg/cm ²)	Up to 200lb load	Front: 28 (2.0)
		Rear: 28 (2.0)
	Up to vehicle capacity load	Front: 32 (2.25)
		Rear: 40 (2.8)
Vehicle capacity load limit	360lbs (163 kg)	
Tire size	Front: 3.25H19 Rear: 4.00H18	
Tire brand	Front: Bridgestone S21F2 Dunlop F6 Rear: Bridgestone S21R2 Dunlop K87 Mark II	

WARNING:

- The use of tires other than those recommended may result in decreased

stability and handling.

- Improper inflation of the tires will cause abnormal tread wear or other damage and create a safety hazard. Riding with underinflated tires will cause the tires to slip on the rims damaging the inner tube valves. Severe underinflation may result in loss of the tire from the rim.
- Check tire pressures frequently and adjust if necessary.
- It is recommended that the tires be replaced when the tread depth at the center of the tire is less than the following limit.

Minimum recommend tire center tread depth
Front: 1/16 in. (1.5 mm) Rear: 3/32 in. (2.0 mm)

- Operation with excessively worn tires is very hazardous and will adversely affect traction, steering and handling.