

■ Service Data

Tyre size	Front	130/70R18M/C 63V
	Rear	200/50R17M/C 75V
Tyre type	Radial, tubeless	
Recommended Tyres	Front	DUNLOP D423F BRIDGESTONE G853 RADIAL F
	Rear	DUNLOP D423 BRIDGESTONE G852 RADIAL F
Tyre air pressure	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
	Rear	290 kPa (2.90 kgf/cm ² , 42 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	(standard)	CR7EH-9 (NGK) or U22FER9 (DENSO)
	(For extended high speed riding)	CR8EH-9 (NGK) or U24FER9 (DENSO)
Spark plug gap	0.80 to 0.90 mm (0.031 to 0.035 in)	
Idle speed	1,000 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	After draining	3.6 litres (3.8 US qt, 3.2 Imp qt)
	After draining & engine oil filter change	3.9 litres (4.1 US qt, 3.4 Imp qt)
	After disassembly	4.7 litres (5.0 US qt, 4.1 Imp qt)
Recommended final drive oil	Hypoid gear oil SAE 80	
Final drive oil capacity	After draining	155 cm ³ (5.2 US oz, 5.5 Imp oz)
	After disassembly	175 cm ³ (5.9 US oz, 6.2 Imp oz)
Recommended brake (clutch) fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	3.00 litres (3.17 US qt, 2.64 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	