

## TIRES: TUBELESS

This motorcycle is equipped with tubeless tires, valves, and wheel rims. Use only tires marked "TUBELESS" and tubeless valves on rims marked "TUBELESS TIRE APPLICABLE".

Cold tire pressures kg/cm <sup>2</sup> (psi)	Up to 90 kg (200 lb) load	Front: 1.75 (24) Rear: 2.0 (28)
	Up to vehicle capacity load	Front: 1.75 (24) Rear: 2.5 (36)
Vehicle capacity load limit	150 kg (330 lbs)	
Tire size	Front: 3.25S19-4PR Rear: 3.75S18-4PR	
Tire brand	Front: YOKOHAMA Y-992 BRIDGESTONE S703 TUBELESS ONLY Rear: YOKOHAMA Y-987 BRIDGESTONE S21R2 TUBELESS ONLY	

### Inspection:

Proper air pressure will provide maximum stability, riding comfort and tire life. Check tire pressures frequently and adjust if necessary.

### **NOTE:**

- \* Check tire pressure when the tires are "Cold" before you ride.

Check the tires for cuts, imbedded nails or other sharp objects. Check the rims for dents or deformation. If there is any damage, see your authorized Honda dealer for repair, replacement, and balancing.

### **WARNING**

- \* *Improper tire inflation will cause abnormal tread wear and create a safety hazard. Underinflation may result in the tire slipping on, or coming off of the rim.*
- \* *Operation with excessively worn tires is hazardous and will adversely affect traction and handling.*