

## 5. SPECIFICATIONS

Item	Metric	English
<b>Dimension</b>		
Overall length	1,225 mm	48.2 in
Overall width	610 mm	24.0 in
Overall height	725 mm	28.5 in
Wheelbase	845 mm	33.2 in
Seat height	495 mm	19.5 in
Ground clearance	115 mm	4.5 in
Dry weight	35 kg	77.2 lb
<b>Frame</b>		
Type	Double cradle (Bolt-on)	
F. suspension, travel	Telescopic fork, travel 60 mm (2.4 in)	
R. suspension, travel	Unit swing mono shock	
F. tyre size, pressure	2.50—10, 100 kPa (1.0 kg/cm <sup>2</sup> , 14 psi)	
R. tyre size, pressure	2.50—10, 100 kPa (1.0 kg/cm <sup>2</sup> , 14 psi)	
Fuel capacity	2.0 ℓ	0.53 US gal 0.44 Imp gal
Caster angle	65°	
Trail length	51 mm	2.0 in
<b>Engine</b>		
Type	Air cooled, 2-stroke	
Cylinder arrangement	Horizontal single	
Bore and stroke	40 x 39.3 mm	1.57 x 1.55 in
Displacement	49.4 cm <sup>3</sup>	3.0 cu-in
Compression ratio	7.2 : 1	
Transmission oil capacity	0.75 ℓ	0.79 US qt 0.66 Imp qt
Idle speed	1800 min <sup>-1</sup>	1800 rpm