MAINTENANCE SCHEDULE This maintenance schedule is based upon average riding conditions. Machines subjected to severe use, or	INITIAL SERVICE PERIOD				
ridden in unusually dusty areas, require more frequent servicing.	500 miles	1 month 500 miles	3 months 1,500 miles	6 months 3,000 miles	
ENGINE OIL—Change			0		
CENTRIFUGAL OIL FILTER—Clean					
OIL FILTER SCREEN—Clean					
SPARK PLUG—Clean and adjust gap or replace if necessary				0	
CONTACT POINTS AND IGNITION TIMING—Clean, check, and adjust or replace if necessary.	•			0	
*VALVE TAPPET CLEARANCE—Check, and adjust if necessary	•			0	
*CAM CHAIN TENSION—Adjust					
POLYURETHANE FOAM AIR FILTER ELEMENT— Clean and oil	(Service mo	Service more frequently if operated in dusty areas			
*CARBURETOR—Check, and adjust if necessary				0	
THROTTLE OPERATION—Inspect cable Check, and adjust free play	•			0	
FUEL FILTER SCREEN—Clean					
FUEL LINES—Check				0	
*CLUTCH—Check operation, and adjust if necessary				ŏ	
DRIVE CHAIN—Check, lubricate, and adjust if necessary	**	0			