

Specifications

| Capacities | |
|-------------------------|--|
| passenger capacity | operator only |
| maximum weight capacity | 110 kg (243 lbs) rider, all cargo and accessories |

| Engine Specifications | |
|------------------------------|--|
| displacement | 229 cm ³ (14.0 cu-in) |
| bore & stroke | 68.5 × 62.2 mm (2.70 × 2.45 in) |
| compression ratio | 9.2 : 1 |
| spark plug (standard) | DPR8EA-9 (NGK) or X24EPR-U9 (DENSO) |
| spark plug (cold climate) | DPR7EA-9 (NGK) or X22EPR-U9 (DENSO) |
| spark plug gap | 0.80 – 0.90 mm (0.031 – 0.035 in) |
| valve clearance (cold) | 0.13 mm (0.005 in) |
| idle speed | 1,400 ± 100 min ⁻¹ (rpm) |

| Power Transmission | | |
|---------------------------|---------|-------|
| primary reduction | | 3.086 |
| final reduction | | 3.692 |
| gear ratio | 1st | 2.846 |
| | 2nd | 1.933 |
| | 3rd | 1.444 |
| | 4th | 1.130 |
| | 5th | 0.913 |
| | reverse | 4.769 |
| final drive | | shaft |