

SPECIFICATIONS

DIMENSIONS	
Overall length	1,720 mm (67.7 in)
Overall width	1,105 mm (43.5 in)
Overall height	1,085 mm (42.7 in)
Wheelbase	1,150 mm (45.3 in)
WEIGHT	
Dry Weight	171 kg (377 lbs)
CAPACITIES	
Engine oil	2.0 ℓ (2.1 US qt , 1.8 Imp qt)
Fuel tank	8.5 ℓ (2.25 US gal , 1.87 Imp gal)
Fuel reserve	1.8 ℓ (0.48 US gal , 0.40 Imp gal)
ENGINE	
Bore and stroke	74 × 65.5 mm (2.91 × 2.58 in)
Compression ratio	8.9 : 1
Displacement	281.7 cm ³ (17.18 cu-in)
Engine idle speed	1,400 ± 100 rpm
Spark plug, standard	DR8ES-L (NGK) X24ESR-U (NIPPONDENSO)
Spark plug gap	0.60–0.70 mm (0.024–0.028 in)
Valve clearance	0.10 mm (0.004 in)
CHASSIS AND SUSPENSION	
Caster angle	7°
Trail length	32 mm (1.3 in)
Tire size, Front	AT 22 × 7-10 ★★
Rear	AT 22 × 10-9 ★