

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING [NOTE (3)]							PAGE
			1,000 km (600 mi)	6,000 km (3,750 mi)	12,000 km (7,500 mi)	18,000 km (11,250 mi)	24,000 km (15,000 mi)	30,000 km (18,750 mi)	36,000 km (22,500 mi)	
		EVERY								
* FUEL LINES					I		I		I	
* FUEL STRAINER				C	C	C	C	C	C	
* THROTTLE OPERATION					I		I		I	122
* CARBURETOR-CHOKE					I		I		I	
* AIR CLEANER		NOTE (1)			R		R		R	118
CRANKCASE BREATHER		NOTE (2)		C	C	C	C	C	C	128
SPARK PLUGS				I	R	I	R	I	R	114
* VALVE CLEARANCE			I	I	I		I		I	
ENGINE OIL		YEAR	R		R		R		R	108
ENGINE OIL FILTER		YEAR	R		R		R		R	110
* CARBURETOR- SYNCHRONIZATION			I		I		I		I	
* CARBURETOR-IDLE SPEED			I	I	I	I	I	I	I	124
RADIATOR COOLANT					I		I		*R	168
* RADIATOR CORE					I		I		I	
* COOLING SYSTEM HOSES & CONNECTIONS					I		I		I	
DRIVE CHAIN			I, L EVERY 1,000 km (600 mi)							130