

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING [NOTE (3)]							PAGE
			EVERY	1,000 km (600 mi)	6,400 km (4,000 mi)	12,800 km (8,000 mi)	19,200 km (12,000 mi)	25,600 km (16,000 mi)	32,000 km (20,000 mi)	
* FUEL LINES					I		I		I	
* FUEL STRAINER			C	C	C	C	C	C	C	
* THROTTLE OPERATION			I		I		I		I	128
* CARBURETOR-CHOKE					I		I		I	
* AIR CLEANER		NOTE (1)			R		R		R	124
CRANKCASE BREATHER		NOTE (2)		C	C	C	C	C	C	134
SPARK PLUGS				I	R	I	R	I	R	112
* VALVE CLEARANCE			I		I		I		I	116
ENGINE OIL		YEAR	R		R		R		R	106
ENGINE OIL FILTER		YEAR	R		R		R		R	106
* CARBURETOR-SYNCHRONIZATION			I		I		I		I	
* CARBURETOR-IDLE SPEED			I	I	I	I	I	I	I	130
RADIATOR COOLANT					I		I		*R	172
* RADIATOR CORE					I		I		I	
* COOLING SYSTEM HOSES & CONNECTIONS			I		I		I		I	