



SPECIFICATIONS

Dimensions	Overall length	1,795 mm (70.7 in)
	Overall width	1,075 mm (42.3 in)
	Overall height	1,040 mm (40.9 in)
	Wheelbase	1,197 mm (47.1 in)
	Seat height	710 mm (28.0 in)
	Foot peg height	295 mm (11.6 in)
	Ground clearance	115 mm (4.5 in)
	Dry weight	137 kg (302 lb)
	Weight distribution	Front Rear
Frame	Type	Double cradle
	Front suspension and travel	Telescopic fork, 170 mm (6.7 in)
	Rear suspension and travel	Swingarm, Pro-link, 110 mm (4.3 in)
	Front tire size type	22 x 11.0-8 ATV tire
	Front tire pressure	15 kPa (0.15 kg/cm ² , 2.2 psi)
	Rear tire size type	22 x 11.0-8 ATV tire
	Rear tire pressure	15 kPa (0.15 kg/cm ² , 2.2 psi)
	Front brake	Single disc
	Rear brake	Internal expanding shoe
	Fuel capacity	8.4 lit (2.2 US gal, 1.9 Imp gal)
	Fuel reserve capacity	1.9 lit (0.50 US gal, 0.42 Imp gal)
	Caster angle	69°
Trail length	45 mm (1.8 in)	
Front fork oil	174 cc (5.88 US ozs, 4.90 Imp ozs)	
Engine	Type	Air cooled 2 stroke engine
	Cylinder arrangement	Single cylinder 3° inclined from vertical
	Bore x stroke	70 x 64.4 mm (2.756 x 2.353 in)
	Displacement	248 cm ³ (15.07 cu. in)
	Compression ratio	6.6 : 1
	Transmission oil capacity	1.1 lit (1.2 US qt. 1.0 Imp qt)
	Lubrication system	Gasoline/oil mixture
	Fuel required	Gasoline 20 : oil 1 (pre-mixed) (R.O.N. 92-100)
Air filtration	Oiled polyurethane form	