

■ Service Data

Tire size	Front	70/90-17M/C 38P
	Rear	80/90-17M/C 50P
Tire type	Bias-ply, tubeless	
	Recommended Tire	IRC NF63B YD IRC NR94
Tire air pressure	Front	29 psi (200 kPa, 2.00 kgf/cm ²)
	Rear	33 psi (225 kPa, 2.25 kgf/cm ²)
Spark plug	(standard)	CPR6EA-9 (NGK) or U20EPR9 (DENSO)
	(For extended high speed riding)	CPR7EA-9 (NGK) or U22EPR9 (DENSO)

Spark plug gap	0.03 - 0.04 in (0.8 - 0.9 mm)
Idle speed	(non-adjustable) 1,400 ± 100 rpm
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil
Engine oil capacity	After draining 0.8 US qt (0.8 L) After disassembly 1.1 US qt (1.0 L)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent
Drive chain slack	1.0 - 1.4 in (25 - 35 mm)
Standard drive chain	DID420AD2 or RK420EL
No. of links	106
Standard sprocket size	Drive sprocket 14T Driven sprocket 36T