

Specifications

■ Bulb

| | |
|--|-----|
| Headlight | LED |
| Brake light/Taillight | LED |
| Position light | LED |
| Front turn signal light/ Position light | LED |
| Rear turn signal light | LED |
| License plate light | LED |

■ Fuse

| | |
|------------|-------------------------|
| Main fuse | 30 A |
| Other fuse | 30 A, 15 A, 10 A, 7.5 A |

■ Torque Specifications

| | |
|--|---------------------------------|
| Engine oil drain bolt | 22 lbf-ft (30 N·m, 3.1 kgf-m) |
| Oil filter | 19 lbf-ft (26 N·m, 2.7 kgf-m) |
| Bearing holder pinch bolt | 20 lbf-ft (27 N·m, 2.8 kgf-m) |
| Front wheel axle bolt | 58 lbf-ft (79 N·m, 8.1 kgf-m) |
| Front wheel brake caliper mounting bolt | 33 lbf-ft (45 N·m, 4.6 kgf-m) |
| Front wheel axle pinch bolt | 16 lbf-ft (22 N·m, 2.2 kgf-m) |
| Muffler mount bolt and nut | 16 lbf-ft (22 N·m, 2.2 kgf-m) |
| Right step bracket bolt A | 27 lbf-ft (37 N·m, 3.8 kgf-m) |
| Right step bracket bolt B | 27 lbf-ft (37 N·m, 3.8 kgf-m) |
| Muffler band bolt | 16 lbf-ft (22 N·m, 2.2 kgf-m) |
| Rear wheel nut | 80 lbf-ft (108 N·m, 11.0 kgf-m) |