Specifications

■ Main Components

I Main Components			
Туре	SC60		
Overall length	83.5 in (2,120 mm)		
Overall width	31.7 in (805 mm)		
Overall height	43.1 in (1,095 mm)		
Wheelbase	56.9 in (1,445 mm)		
Minimum ground clearance	5.1 in (130 mm)		
Caster angle	25° 00′		
Trail	3.9 in (99 mm)		
Curb weight	CB1000R	485 lb (220 kg)	
	CB1000RA		
	USA model	496 lb (225 kg)	
	Canada model	496 lb (224 kg)	
Maximum weight capacity*1	384 lb (174 kg)		
Passenger capacity	Rider and 1 passenger		
Minimum turning radius	9.2 ft (2.8 m)		
Displacement	60.9 cu-in (998 cm³)		
Bore x stroke	2.95 × 2.22 in (75.0 x 56.5 mm)		
Compression ratio	11.2:1		

^{*1} Including rider, passenger, all luggage, and accessories

	Unleaded gasoline		
Fuel	Recommend	commended fuel octane number:	
	Pump Octane Number (PON) 86 or higher.		
Tank capacity	4.5 US gal (17 liters)		
Battery	YTZ10S 12V-8.6Ah (10HR)		
Gear ratios	1st	2.538	
	2nd	1.941	
	3rd	1.578	
	4th	1.363	
	5th	1.217	
	6th	1.115	
Reduction ratios (primary / final)		1.604 / 2.750	
·	-	<u></u>	