

Specifications

■ Service Data

Tire size	Front	110/70-17M/C 54S	
	Rear	140/70-17M/C 66S	
Tire type	Bias-ply, tubeless		
Recommended Tires	Front	IRC RX-01FD	
	Rear	IRC RX-01RZ	
Tire air pressure	Up to maximum weight	Front 29 psi (200 kPa, 2.00 kgf/cm ²)	
	capacity	Rear 33 psi (225 kPa, 2.25 kgf/cm ²)	
	Up to 200 lb (90 kg) load	Front	29 psi (200 kPa, 2.00 kgf/cm ²)
		Rear	29 psi (200 kPa, 2.00 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)	
	Rear	0.08 in (2.0 mm)	
Spark plug	(standard)	SIMR8A9 (NGK)	
Spark plug gap	(non-adjustable)	0.031 to 0.035 in (0.80 to 0.90 mm)	
Idle speed	(non-adjustable)	1,400 ± 100 rpm	

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	After draining	1.5 US qt (1.4 liters)
Engine oil capacity	After draining & engine oil filter change	1.6 US qt (1.5 liters)
	After disassembly	1.9 US qt (1.8 liters)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	1.16 US qt (1.10 liters)	
Recommended coolant	Pro Honda HP Coolant	