

Specifications

■ Main Components

Type	PC45	
Overall length	81.7 in (2,075 mm)	
Overall width	30.7 in (780 mm)	
Overall height	41.7 in (1,060 mm)	
Wheelbase	55.5 in (1,410 mm)	
Minimum ground clearance	6.1 in (155 mm)	
Caster angle	25° 30'	
Trail	4.0 in (102 mm)	
Curb weight	CB500F	
	49 STATE	419 lb (190 kg)
	50 STATE (meets California)	421 lb (191 kg)
	CB500FA	
	49 STATE	423 lb (192 kg)
	50 STATE (meets California)	425 lb (193 kg)
Canada model	423 lb (192 kg)	
Maximum weight capacity*1	370 lb (168 kg)	
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	8.9 ft (2.7 m)	

*1 Including rider, passenger, all luggage, and accessories

Displacement	28.7 cu-in (471 cm ³)	
Bore x stroke	2.64 x 2.63 in (67.0 x 66.8 mm)	
Compression ratio	10.7:1	
Fuel	Unleaded gasoline Recommended: 86 PON or higher	
Tank capacity	4.15 US gal (15.7 liters)	
Battery	FTZ10S	
	12V-8.6Ah (10 HR)	
	YTZ10S	
	12V-8.6Ah (10 HR)	
Gear ratios	1st	3.285
	2nd	2.105
	3rd	1.600
	4th	1.300
	5th	1.150
	6th	1.043
Reduction ratios (primary / final)	2.029 / 2.733	