

Specifications

Standard sprocket size	Drive sprocket	14T
	Driven sprocket	36T

■ Bulbs

Headlight	12 V-55 W x 2
Brake Light/Taillight	12 V-21/5 W
Front turn signal light	12 V-21 W x 2
Rear turn signal light	12 V-21 W x 2
License plate light	12 V-5 W

■ Fuses

Main fuse	30 A
Other fuse	CBR300R 15 A, 10 A
	CBR300RA 30 A, 15 A, 10 A

■ Torque Specifications

Oil filter cover bolt	9 lbf-ft (12 N-m, 1.2 kgf-m)
Engine oil drain bolt	18 lbf-ft (24 N-m, 2.4 kgf-m)
Air cleaner case cover screw	0.8 lbf-ft (1.1 N-m, 0.1 kgf-m)
Rear axle nut	65 lbf-ft (88 N-m, 9.0 kgf-m)
Drive chain adjusting lock nut	15 lbf-ft (21 N-m, 2.1 kgf-m)
Front axle nut	44 lbf-ft (59 N-m, 6.0 kgf-m)
Brake caliper mounting bolt	22 lbf-ft (30 N-m, 3.1 kgf-m)
Front axle pinch bolt	16 lbf-ft (22 N-m, 2.2 kgf-m)