

Specifications

■ Main Components

Overall length	91.9 in (2,335 mm)
Overall width	36.6 in (930 mm)
Overall height	58.1 in (1,475 mm)
Wheelbase	62.0 in (1,575 mm)
Minimum ground clearance	9.8 in (250 mm)
Caster angle	27.5°
Trail	4.4 in (113 mm)
Curb weight	CRF1000A 511 lb (232 kg)
	CRF1000D 534 lb (242 kg)
Maximum weight capacity*1	392 lb (178 kg)
Maximum weight on rear carrier	22 lb (10 kg)
Passenger capacity	Rider and 1 passenger
Minimum turning radius	8.5 ft (2.6 m)

*1 Including rider, passenger, all luggage, and accessories

Displacement	60.9 cu-in (999 cm ³)
Bore x stroke	3.62 x 2.96 in (92.0 x 75.1 mm)
Compression ratio	10.0:1
Fuel	Unleaded gasoline Recommended: 86 PON or higher
Tank capacity	4.97 US gal (18.8 liters)
Battery	YTZ14S
	12V-11.2Ah (10 HR)
CRF1000A	
	1st 2.866
	2nd 1.888
	3rd 1.480
	4th 1.230
	5th 1.100
	6th 0.968
Gear ratios	CRF1000D
	1st 2.562
	2nd 1.761
	3rd 1.375
	4th 1.133
	5th 0.972
	6th 0.882
Reduction ratios (primary / final)	CRF1000A 1.733 / 2.625
	CRF1000D 1.883 / 2.625