

# Specifications

## ■ Main Components

Overall length	<b>CRF1000A/D</b>	91.7 in (2,330 mm)
	<b>CRF1000A II/D II</b>	92.1 in (2,340 mm)
Overall width		36.6 in (930 mm)
Overall height	<b>CRF1000A/D</b>	58.1 in (1,475 mm)
	<b>CRF1000A II/D II</b>	61.8 in (1,570 mm)
Wheelbase	<b>CRF1000A/D</b>	62.0 in (1,575 mm)
	<b>CRF1000A II/D II</b>	62.2 in (1,580 mm)
Minimum ground clearance	<b>CRF1000A/D</b>	9.8 in (250 mm)
	<b>CRF1000A II/D II</b>	10.6 in (270 mm)
Caster angle		27° 30'
Trail		4.4 in (113 mm)

Curb weight	<b>CRF1000A</b>	<b>AC, II AC, III AC</b>
		507 lb (230 kg)
		<b>CM, II CM, III CM</b>
		505 lb (229 kg)
	<b>CRF1000D</b>	<b>AC, II AC, III AC</b>
		529 lb (240 kg)
		<b>CM, II CM, III CM</b>
		527 lb (239 kg)
	<b>CRF1000A II</b>	<b>IV AC</b>
		536 lb (243 kg)
		<b>IV CM</b>
		534 lb (242 kg)
	<b>CRF1000D II</b>	<b>IV AC</b>
		558 lb (253 kg)
		<b>IV CM</b>
		556 lb (252 kg)
Maximum weight capacity *1	<b>CRF1000A/D</b>	437 lb (198 kg)
		<b>CRF1000A II/D II</b>

\*1: Including rider, passenger, all luggage, and accessories