

Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	1.91 US qt (1.81 L)	
Recommended coolant	Pro Honda HP Coolant	
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent	
Drive chain slack	1 3/8 - 1 3/4 in (35 - 45 mm)	
Standard drive chain	DID 525HV3	
	No. of links	124
Standard sprocket size	Drive sprocket	16T
	Driven sprocket	42T

■ Bulbs

Headlight	LED
Cornering light CRF1100A4/D4	LED
Brake light/Taillight	LED
Front turn signal	LED
Rear turn signal	LED
License plate light	LED

■ Fuses

Main fuse	30 A
Other fuse	30 A, 20 A, 15 A, 10 A

■ Torque Specifications

Skid plate bolt A	19 lbf-ft (26 N·m, 2.7 kgf-m)
Skid plate bolt B CRF1100A4/D4	9 lbf-ft (12 N·m, 1.2 kgf-m)
Spark arrester mounting bolt	6.6 lbf-ft (9.0 N·m, 0.9 kgf-m)
Bolt	6.6 lbf-ft (9.0 N·m, 0.9 kgf-m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf-m)
Engine oil drain bolt	22 lbf-ft (30 N·m, 3.1 kgf-m)
Clutch oil filter cover bolt CRF1100D/D4	9 lbf-ft (12 N·m, 1.2 kgf-m)
Rear wheel axle nut	74 lbf-ft (100 N·m, 10.2 kgf-m)
Drive chain adjusting lock nut	20 lbf-ft (27 N·m, 2.8 kgf-m)
Front wheel axle nut	48 lbf-ft (65 N·m, 6.6 kgf-m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf-m)
Front wheel brake caliper mounting bolt	33 lbf-ft (45 N·m, 4.6 kgf-m)