

Specifications

CRF1100A/D BRIDGESTONE BATTLAX ADVENTURECROSS TOURER AX41TF G	Front	METZELER KAROO STREET
		CRF1100A4/D4 BRIDGESTONE BATTLAX ADVENTURECROSS TOURER AX41TF L
Recommended Tire	Rear	METZELER KAROO STREET
		CRF1100A/D BRIDGESTONE BATTLAX ADVENTURECROSS TOURER AX41TR G
Tire air pressure (Up to 90 kg (200 lbs) load)	Front	33 psi (225 kPa, 2.25 kgf/cm ²)
	Rear	36 psi (250 kPa, 2.50 kgf/cm ²)
Tire air pressure (Up to maximum weight capacity)	Front	33 psi (225 kPa, 2.25 kgf/cm ²)
	Rear	41 psi (280 kPa, 2.80 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)

Spark plug	(standard) SILMAR8A9S (NGK)
Spark plug gap	(non-adjustable) 0.03 - 0.04 in (0.8 - 0.9 mm)
Idle speed	(non-adjustable) 1,250 ± 100 rpm
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil
Engine oil capacity	CRF1100A/A4 After draining 4.1 US qt (3.9 L)
	After draining & engine oil filter change 4.2 US qt (4.0 L)
	After disassembly 5.1 US qt (4.8 L)
	CRF1100D/D4 After draining 4.2 US qt (4.0 L)
Engine oil capacity	After draining & engine oil filter change 4.4 US qt (4.2 L)
	After draining, engine & clutch oil filter change 4.4 US qt (4.2 L)
Engine oil capacity	After disassembly 5.5 US qt (5.2 L)

Specifications