

Quick Reference

Initial Maintenance	About 100 miles (150 km) or 1 month.
Regular Maintenance	About every 600 miles (1,000 km) or 6 months.
Pre-ride Inspection	Check the following items each time before you ride (page 24): tires, spokes & rims, leaks, engine oil, fuel, drive chain, cables, nuts & bolts, spark plug & cap, throttle, brakes, and clutch lever.
Fuel/Capacity	Premium unleaded gasoline, pump octane number of 91 or higher Tank: 1.90 US gal (7.2 ℓ) Reserve: 0.42 US gal (1.6 ℓ)
Engine Oil	API Service Classification SG or higher except oils labeled as energy conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada), or Honda 4-stroke oil, or an equivalent motorcycle oil
Maximum Weight Capacity	220 lb (100 kg) rider only (no passenger or cargo) and any accessories
Tires	Front: 70/100 – 19 NHS 42M Rear: 90/100 – 16 NHS 51M Type: bias-ply, tube
Tire Pressure (cold)	Front: 15 psi (100 kPa, 1.0 kgf/cm ²) Rear: 15 psi (100 kPa, 1.0 kgf/cm ²)
Spark Plug	CPR8EA-9 (NGK)
Fuse	Main: 7.5 A