

Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains	
Drive chain slack	25 to 35 mm (1.0 to 1.4 in)	
Standard drive chain	DID 520VF	
	No. of links	106
Standard sprocket sizes	Engine sprocket	14T
	Rear wheel sprocket	40T

■ Bulbs

Headlight	12V-60/55W
Brake/Tail light	12V-21/5W
Front turn signal lights	12V-21W × 2
Rear turn signal lights	12V-21W × 2
Position light	12V-5W

■ Fuses

Main fuse	30A
Other fuses	10A, 5A

■ Torque Specifications

Hook bolts	21 N·m (2.1 kgf·m, 15 lbf·ft)
Engine oil drain bolt	24 N·m (2.4 kgf·m, 18 lbf·ft)
Oil filter cover bolts	12 N·m (1.2 kgf·m, 9 lbf·ft)
Front wheel axle shaft	73.5 N·m (7.5 kgf·m, 54 lbf·ft)
Front wheel axle pinch bolts	20 N·m (2.0 kgf·m, 15 lbf·ft)
Rear wheel axle nut	88 N·m (9.0 kgf·m, 65 lbf·ft)
Drive chain adjusting lock nuts	27 N·m (2.8 kgf·m, 20 lbf·ft)