

This section tells you how to fine tune your CRF for maximum competition performance.

Initial suspension adjustments should be performed after a minimum of 1 hour of easy break-in time.

Optional rear suspension springs are available in order to tailor your CRF specifically for your weight, riding style and course conditions.

Follow the instructions given in the rear suspension sag setting section of *Rear Suspension Adjustments* to determine if your combined rider and sprung machine weight (rider fully dressed for competition and machine filled coolant, oil and fuel levels ready for competition) requires an optional stiffer or softer rear spring. The need for either optional rear spring may need to be balanced by adjusting the left fork air pressure and oil capacity.

Engine Mode Select Button	120
Current Mode	120
Mode Selection	120
Front Suspension Adjustments	121
Front Suspension Air Pressure	121
Front Suspension Damping (Right Fork)	122
Fork Springs (Left Fork)	122
Fork Removal	125
Right Fork Disassembly	127
Damper Oil Change	129
Right Fork Assembly	131
Fork Installation	133
Rear Suspension Adjustments	137
Rear Suspension Spring Pre-Load	137
Rear Suspension Damping	138
Rear Suspension Race Sag	139
Suspension Adjustments for Track Conditions	141
Suspension Adjustment Guidelines	142
Tuning Tips	145
Spark Plug Reading	145
Steering Damper Adjustment	146
Steering Damper Damping	146
Steering Damper Adjustment Guidelines	147
Chassis Adjustments	148
Rear End	148
Fork Height/Angle	148
Wheelbase	148
Gearing	149
Tire Selection for Track Conditions	150
Personal Fit Adjustments	151
Control Positioning	151
Handlebar Position, Width & Shape	151