

■ Service Data

Tyre size	Front	90/80-17M/C 46P
	Rear	120/70-17M/C 58P
Tyre type	Bias-ply, tubeless	
Recommended Tyres	Front	IRC NF66
	Rear	IRC NR83
Tyre air pressure	Front	200 kPa (2.00 kgf/cm ² , 29 psi)
	Rear	225 kPa (2.25 kgf/cm ² , 33 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	MR9C-9N (NGK) or U27EPR-N9 (DENSO)	
Spark plug gap	0.80 - 0.90 mm (0.031 - 0.035 in)	
Idle speed	1,500 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	
Engine oil capacity	After draining	1.1 L (1.2 US qt, 1.0 Imp qt)
	After disassembly	1.3 L (1.4 US qt, 1.1 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	0.57 L (0.60 US qt, 0.50 Imp qt)	

Recommended coolant	HONDA PRE-MIX COOLANT	
Recommended drive chain lubricant	Drive chain lubricant If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	25 - 35 mm (1.0 - 1.4 in)	
Standard drive chain	RK 428HSB	
	No. of links	120
Standard sprocket sizes	Drive sprocket	15T
	Driven sprocket	44T