

Specifications

Service Data

Tyre size	Front	80/100-18M/C 47P
	Rear	90/90-18M/C 51P
Tyre type	Bias-ply, tube	
Recommended Tyres	Front	MBPSTAR MP-217
	Rear	MBPSTAR MP-218
Tyre air pressure	Front	(Driver only)
		175 kPa (1.75 kgf/cm ² , 25 psi) (Driver and passenger)
	Rear	175 kPa (1.75 kgf/cm ² , 25 psi) (Driver only)
		200 kPa (2.00 kgf/cm ² , 29 psi) (Driver and passenger) 225 kPa (2.25 kgf/cm ² , 33 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plug	(standard)	CPR8EA-9 (NGK)
	(For extend high speed riding)	CPR9EA-9 (NGK)
Spark plug gap	(For cold climate)	CPR7EA-9 (NGK)
	Idle speed	0.8 to 0.9 mm (0.03 to 0.04 in) 1,400 ± 100 rpm

Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	
	After draining	1.0 litres (1.06 US qt, 0.88 Imp qt)
Engine oil capacity	After disassembly	1.2 litres (1.27 US qt, 1.06 Imp qt)
	Recommended drive chain lubricant	Drive chain lubricant. If not available, use SAE 80 or 90 gear oil.
Drive chain slack	20 to 30 mm (0.8 to 1.2 in)	
Standard drive chain	Standard drive chain	HUZHOU SHUANSHI 428H KMC 428HDF
	No. of links	120
Standard sprocket size	Drive sprocket	15T
	Driven sprocket	43T

Specifications