

# Specifications

| <b>Electrical</b> |                            |
|-------------------|----------------------------|
| battery           | YTX14-BS 12 V-12 Ah (10HR) |
| generator         | 0.410 kW/5,000 rpm         |

| <b>Lights</b>                           |   |
|---|---|
| headlight                               | 12 V 30/30 W×2                                |
| brake/tail light                        | LED   |
| neutral indicator                       | 12 V 3.4 W ..... AC type<br>LED ..... CM type |
| reverse indicator                       | 12 V 3.4 W ..... AC type<br>LED ..... CM type |
| high coolant/oil temperature indicator  | 12 V 3.4 W ..... AC type<br>LED ..... CM type |
| low fuel indicator                      | 12 V 3.4 W                                    |
| PGM-FI malfunction indicator lamp (MIL) | 12 V 3.4 W ..... AC type<br>LED ..... CM type |
| parking brake indicator                 | 12 V 3.4 W                                    |
| 4WD indicator                           | 12 V 3.4 W ..... AC type<br>LED ..... CM type |
| front differential lock indicator       | 12 V 3.4 W                                    |

| <b>Fuses</b> |                 |
|--------------|-----------------|
| main         | 30 A            |
| circuit      | 15 A×2 , 10 A×4 |