

Safety Labels

Safety and information labels on your motorcycle provide important safety information and may warn you of potential

hazards that could cause serious injury. Read these labels carefully and don't remove them. If a label comes off or becomes hard to read, contact your dealer for a replacement.

TIRE INFORMATION		
Cold tire pressures : !Up to maximum weight capacity! Front 225kPa 2,25kgf/cm ² 33psi Rear 250kPa 2,50kgf/cm ² 36psi !Up to 90kg(200lbs) load! Front 225kPa 2,25kgf/cm ² 33psi Rear 250kPa 2,50kgf/cm ² 36psi Maximum weight capacity :157kg(346lbs) Tire size : Front 120/70ZR18M/C(59W) Rear 200/50ZR17M/C(75W)	Tire brand DUNLOP	Front D423F K Rear D423 K
Min. recommend tire center tread depth. Front 1,5mm(0,06in.) Rear 2,0mm(0,08in.)		
Read owner's manual.		
This motorcycle is equipped with tubeless tires.		

Cargo Limit
3.0kg / 6.6lbs

CARGO LIMIT
2.0kg / 4.5lbs

DANGER
WARNING
危険

- ▶ NEVER OPEN WHEN HOT.
Hot coolant will scald you.
- ▶ N'OUVREZ PAS QUAND CHAUD
- ▶ NICHT BEI HEISSEN MOTOR OFFNEN.
- ▶ 熱い時あけない下さい。
- ▶ 高温時、请勿打开

1.1