

■ Service Data

Tire size	Front	120/70ZR17M/C (58W)
	Rear	160/60ZR17M/C (69W)
Tire type	Radial, tubeless	
Recommended Tires	Front	PIRELLI SCORPION TRAIL E DUNLOP D609F
	Rear	PIRELLI SCORPION TRAIL DUNLOP D609
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm ²)
	Rear	42 psi (290 kPa, 2.90 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	IFR6G-11K (NGK)
Spark plug gap	(non-adjustable)	0.039 to 0.043 in (1.00 to 1.10 mm)
Idle speed	1,200 ± 100 rpm	
Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	

Engine oil capacity	NC700X	
	After draining	3.3 US qt (3.1 liters)
	After draining & engine oil filter change	3.6 US qt (3.4 liters)
	After disassembly	3.9 US qt (3.7 liters)
	NC700XD	
	After draining	3.4 US qt (3.2 liters)
	After draining & engine oil filter change	3.6 US qt (3.4 liters)
	After draining, engine & clutch oil filter change	3.6 US qt (3.4 liters)
	After disassembly	4.3 US qt (4.1 liters)
	Recommended brake fluid	Honda DOT 4 Brake Fluid
Cooling system capacity	1.79 US qt (1.69 liters)	
Recommended coolant	Pro Honda HP Coolant	