

Specifications

■ Service Data

| | | |
|------------------------|------------|--|
| Tire size | Front | 80/100-10 46J |
| | Rear | 80/100-10 46J |
| Tire type | | Bias-ply, tubeless |
| Recommended Tire | Front | CHENG SHIN C-6161 |
| | Rear | CHENG SHIN C-6161 |
| Tire air pressure | Front | 18 psi (125 kPa, 1.25 kgf/cm ²) |
| | Rear | 29 psi (200 kPa, 2.00 kgf/cm ²) |
| Spark plug | (standard) | CPR8EA-9 (NGK) |
| Spark plug gap | | 0.031 - 0.035 in (0.80 - 0.90 mm) |
| Idle speed | | 2,000 ± 100 rpm |
| Recommended engine oil | | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MB, Pro Honda HP4M 4-stroke oil or an equivalent motorcycle oil |

| | | |
|-------------------------|--|----------------------|
| Engine oil capacity | After draining | 0.69 US qt (0.65 L) |
| | After draining & engine oil strainer screen cleaning | 0.69 US qt (0.65 L) |
| | After disassembly | 0.74 US qt (0.7 L) |
| Cooling system capacity | | 0.33 US qt (0.31 L) |
| Recommended coolant | | Pro Honda HP Coolant |

■ Bulbs

| | |
|-----------------------|---------------|
| Headlight | 12 V-35/35 W |
| Brake light/Taillight | 12 V-21/5 W |
| Front turn signal | 12 V-10 W x 2 |
| Rear turn signal | 12 V-10 W x 2 |

■ Fuses

| | |
|------------|------|
| Main fuse | 25 A |
| Other fuse | 10 A |

■ Torque Specifications

| | |
|---------------------------------|---------------------------------|
| Engine oil drain bolt | 18 lbf-ft (24 N-m, 2.4 kgf-m) |
| Engine oil plug | 15 lbf-ft (20 N-m, 2.0 kgf-m) |
| Air cleaner housing cover screw | 0.8 lbf-ft (1.1 N-m, 0.1 kgf-m) |