

Quick Reference

Tires	<p>Front: SXS1000M3/M3P/M5P 27X9.00-12 NHS BLACKSTONE OTR HP-009 SXS1000M3L/M5D/M5L 27X9.00R14 NHS MAXXIS BIGHORN 2.0</p> <p>Rear: SXS1000M3/M3P/M5P 27X11.00-12 NHS BLACKSTONE OTR HP-009 SXS1000M3L/M5D/M5L 27X11.00R14 NHS MAXXIS BIGHORN 2.0</p>
Tire Pressure (cold)	<p>Front: SXS1000M3/M3P/M5P/M5D 13 psi (90 kPa) SXS1000M3L/M5L 14 psi (100 kPa)</p> <p>Rear: 14 psi (100 kPa)</p>
Spark Plugs	<p>standard: SILMAR7A9S (NGK)</p>
Coolant	Ethylene glycol antifreeze (silicate-free) for aluminum engines in 50/50 solution with Pro Honda HP Coolant or an equivalent distilled water
Fuses	<p>main: 50 A</p> <p>circuit: SXS1000M3/M3P/M5P/M5D 30 A, 20 A, 15 A × 4, 10 A × 3 SXS1000M3L/M5L 30 A × 2, 20 A, 15 A × 4, 10 A × 3</p> <p>EPS (except for SXS1000M3): 40 A BTCS (SXS1000M3L/M5L only): 40 A</p>