

■ Bulbs

Headlight	12V-60/55W
Brake/Taillight	LED
Front turn signal lights	12V-21/5W x 2
Rear turn signal lights	12V-21W x 2
License plate light	12V-5W

■ Fuses

Main fuse	30A	
Other fuses	VT1300CX	20A, 10A
	VT1300CXA	30A, 20A, 10A

■ Torque Specifications

Seat mounting bolts B	16 lbf·ft (22 N·m, 2.2 kgf·m)
Oil filter	19 lbf·ft (26 N·m, 2.7 kgf·m)
Engine oil drain bolt	22 lbf·ft (30 N·m, 3.1 kgf·m)
Air cleaner housing cover bolts	1.1 lbf·ft (1.5 N·m, 0.2 kgf·m)
Final drive oil fill hole cap	9 lbf·ft (12 N·m, 1.2 kgf·m)
Final drive oil drain bolt	9 lbf·ft (12 N·m, 1.2 kgf·m)
Headlight bolts and nuts	7 lbf·ft (10 N·m, 1.0 kgf·m)
Front wheel axle pinch bolts	16 lbf·ft (22 N·m, 2.2 kgf·m)
Front wheel axle bolt	47 lbf·ft (64 N·m, 6.5 kgf·m)
Front wheel caliper fixing bolts	23 lbf·ft (31 N·m, 3.2 kgf·m)
Rear brake bracket bolt	51 lbf·ft (69 N·m, 7.0 kgf·m)
Rear wheel axle nut	94 lbf·ft (127 N·m, 13.0 kgf·m)
Rear wheel axle holding bolt	20 lbf·ft (27 N·m, 2.8 kgf·m)
Exhaust pipe joint nuts	17 lbf·ft (23 N·m, 2.3 kgf·m)
Muffler bracket bolt A, B, and nuts	20 lbf·ft (27 N·m, 2.8 kgf·m)