

### ■ Bulbs

Headlight	12 V-60/55 W
Brake light/Taillight	12 V-21/5 W
Front turn signal light	12 V-21/5 W x 2
Rear turn signal light	12 V-21 W x 2
License plate light	12 V-5 W

### ■ Fuses

Main fuse	30 A
FI fuse	15 A
Other fuse	20 A, 10 A

### ■ Torque Specifications

Engine oil drain bolt	21 lbf-ft (29 N·m, 3.0 kgf·m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf·m)
Final drive oil fill hole cap	9 lbf-ft (12 N·m, 1.2 kgf·m)
Final drive oil drain bolt	9 lbf-ft (12 N·m, 1.2 kgf·m)
Front wheel axle bolt	44 lbf-ft (59 N·m, 6.0 kgf·m)
Front wheel axle pinch bolt	16 lbf-ft (22 N·m, 2.2 kgf·m)
Rear brake stopper arm nut	16 lbf-ft (22 N·m, 2.2 kgf·m)
Rear wheel axle nut	65 lbf-ft (88 N·m, 9.0 kgf·m)
Rear wheel axle holding bolt	20 lbf-ft (27 N·m, 2.8 kgf·m)
Exhaust pipe joint nut	18 lbf-ft (25 N·m, 2.5 kgf·m)
Muffler bracket nut	20 lbf-ft (27 N·m, 2.8 kgf·m)
Footpeg bolt A, B and nut	29 lbf-ft (39 N·m, 4.0 kgf·m)