

# Specifications

## ■ Main Components

Type	RC53	
Overall length	<b>VT750C2B</b>	94.3 in (2,395 mm)
	<b>VT750C2/C2F</b>	95.7 in (2,430 mm)
	<b>VT750C2S</b>	98.8 in (2,510 mm)* <sup>1</sup> 95.7 in (2,430 mm)* <sup>2</sup>
Overall width	<b>VT750C2B</b>	32.5 in (825 mm)
	<b>VT750C2/C2F</b>	32.9 in (835 mm)
	<b>VT750C2S</b>	36.2 in (920 mm)* <sup>1</sup> 32.9 in (835 mm)* <sup>2</sup>
Overall height	<b>VT750C2B</b>	42.9 in (1,090 mm)
	<b>VT750C2/C2F/C2S</b>	44.3 in (1,125 mm)
Wheelbase	<b>VT750C2B</b>	64.6 in (1,640 mm)
	<b>VT750C2/C2F</b>	65.2 in (1,655 mm)
	<b>VT750C2S</b>	64.6 in (1,640 mm)* <sup>1</sup> 65.2 in (1,655 mm)* <sup>2</sup>
Minimum ground clearance	5.1 in (130 mm)	
Caster angle	<b>VT750C2B</b>	34° 00'
	<b>VT750C2/C2F</b>	34° 30'
	<b>VT750C2S</b>	34° 30'* <sup>1</sup> 34° 00'* <sup>2</sup>

\*1 49 STATE type

\*2 50 STATE type (meets California)

Trail	6.3 in (161 mm)	
Curb weight	<b>VT750C2B</b>	549 lb (249 kg)* <sup>1, *3</sup> 552 lb (250 kg)* <sup>2</sup>
	<b>VT750C2/C2F</b>	542 lb (246 kg)* <sup>1</sup> 544 lb (247 kg)* <sup>2</sup>
	<b>VT750C2S</b>	573 lb (260 kg)* <sup>1</sup> 555 lb (252 kg)* <sup>2</sup>
Maximum weight capacity* <sup>4</sup>	<b>VT750C2B</b>	401 lb (182 kg)
	<b>VT750C2/C2F</b>	397 lb (180 kg)
	<b>VT750C2S</b>	401 lb (182 kg)* <sup>1</sup> 397 lb (180 kg)* <sup>2</sup>

\*1 49 STATE type

\*2 50 STATE type (meets California)

\*3 Canada

\*4 Including rider, passenger, all luggage, and accessories