

## Specifications

### ■ Service Data

Tire size	Front	90/90-14M/C 46P
	Rear	100/90-14M/C 57P
Tire type		Bias-ply, tubeless
Recommended Tires	Front	IRC SS-560F
	Rear	IRC SS-560R D
Tire air pressure	Front	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> )
		[With less than 200 lb (90 kg) of added weight]
	Rear	33 psi (225 kPa, 2.25 kgf/cm <sup>2</sup> )
		[With more than 200 lb (90 kg) of added weight]
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plug	(standard)	CPR7EA-9 (NGK)
Spark plug gap		0.03 to 0.04 in (0.8 to 0.9 mm)
Idle speed (non-adjustable)		1,700 ± 100 rpm

Recommended engine oil	API Service Classification SJ or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MB, Pro Honda HP4M 4-stroke oil or an equivalent motorcycle oil	
	After draining	0.8 US qt (0.8 liters)
Engine oil capacity	After draining & engine oil strainer screen cleaning	1.0 US qt (0.9 liters)
	After disassembly	1.0 US qt (0.9 liters)
Transmission oil capacity	After draining	0.13 US qt (0.12 liters)
	After disassembly	0.15 US qt (0.14 liters)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Cooling system capacity	0.51 US qt (0.48 liters)	
Recommended coolant	Pro Honda HP Coolant	