

Gear ratios	1st	2.785
	2nd	1.875
	3rd	1.409
	4th	1.120
	5th	0.937
Reduction ratios (primary / final)	XL125LEK	3.350 / 3.187
	XR125LEK	
	XR150LEK	3.350 / 2.882

■ Service Data

Tyre size	Front	XR125LEK	90/90-19M/C 52P
		XR150LEK	
	Rear	XL125LEK	70/100-21M/C 44P
		XR125LEK	110/90-17M/C 60P
		XR150LEK	100/90-18M/C 56P
Tyre type	Bias-ply, tube		
Recommended Tyres	Front	XR125LEK	CHENG SHIN C6559F
		XR150LEK	
	Rear	XL125LEK	CHENG SHIN CM-704
		XR125LEK	CHENG SHIN C6559
		XR150LEK	CHENG SHIN CM-705
Tyre air pressure (Driver only)	Front	150 kPa (1.50 kgf/cm ² , 22 psi)	
	Rear	150 kPa (1.50 kgf/cm ² , 22 psi)	
Tyre air pressure (Driver and passenger)	Front	150 kPa (1.50 kgf/cm ² , 22 psi)	
		XR125LEK	200 kPa
	Rear	XR150LEK	(2.00 kgf/cm ² , 29 psi)
		XL125LEK	225 kPa (2.25 kgf/cm ² , 33 psi)
Minimum tread depth	Front	Except XL125LEK	3.0 mm (0.12 in)
	Rear	Except XL125LEK	3.0 mm (0.12 in)