








| Items | | Frequency | Odometer Reading*1 | | | | | | | Refer to page | |
|----------------------------|--------------------------|---|---|----------|----------|----------|----------|----------|----------|---------------|--------|
| | | | x 1,000 mi | 0.6 | 4 | 8 | 12 | 16 | 20 | | 24 |
| | | | x 1,000 km | 1.0 | 6.4 | 12.8 | 19.2 | 25.6 | 32.0 | | 38.4 |
| Non-Emission-Related Items | Drive Chain*4 | | Every 500 mi (800 km) I L | | | | | | | 65 | |
| | Drive Chain Slider | | | I | I | I | I | I | I | 68 | |
| | Brake Fluid*5 | | | I | I | R | I | I | R | 62 | |
| | Brake Pads Wear | | | I | I | I | I | I | I | 63 | |
| | Brake System | | I | | I | | I | | I | 62 | |
| | Brake Light Switch |  | | | I | | I | | I | 79 | |
| | Headlight Aim |  | | | I | | I | | I | 79 | |
| | Clutch System | | I | I | I | I | I | I | I | 71 | |
| | Side Stand | | I | | I | | I | | I | 64 | |
| | Suspension |  | | | I | | I | | I | - | |
| | Spark Arrester/Muffler |  | | | C | C | C | C | C | C | 61 |
| | Nuts, Bolts, Fasteners |  | | I | | I | | I | | I | - |
| | Wheels/Tires*4 |  | | I | I | I | I | I | I | I | 44, 70 |
| | Steering Head Bearings*4 |  | | I | | I | | I | | I | - |

Notes:

- *1 : At higher odometer readings, repeat at the frequency interval established here.
- *2 : Service more frequently when riding in unusually wet or dusty areas.
- *3 : 50 STATE (meets California).

*4 : Service more frequently when riding OFF-ROAD.

*5 : Replace every 2 years, or at indicated odometer interval, whichever comes first. Replacement requires mechanical skill.