

Specifications

■ Service Data

| | | |
|-------------------------|----------------------------------|---|
| Tire size | Front | 3.00-21 51S |
| | Rear | 4.60-18 63S |
| Tire type | | Bias-ply, tube |
| Recommended Tires | Front | DUNLOP K850 BRIDGESTONE TW-301 |
| | Rear | DUNLOP K850 BRIDGESTONE TW-52 |
| Tire air pressure | Front | 22 psi (150 kPa, 1.50 kgf/cm ²) |
| | Rear | 22 psi (150 kPa, 1.50 kgf/cm ²) |
| Minimum tread depth | Front | 0.12 in (3.0 mm) |
| | Rear | 0.12 in (3.0 mm) |
| Spark plug | (standard) | DPR8EA-9 (NGK) X24EPR-U9 (DENSO) |
| | (cold climate) | DPR7EA-9 (NGK) X22EPR-U9 (DENSO) |
| | (for extended high speed riding) | DPR9EA-9 (NGK) X27EPR-U9 (DENSO) |
| Spark plug gap | | 0.031 - 0.035 in (0.80 - 0.90 mm) |
| Idle speed (In neutral) | | 1,300 ± 100 rpm |

| | | |
|-----------------------------------|---|---------------------|
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil | |
| Engine oil capacity | After draining | 2.0 US qt (1.9 L) |
| | After draining & filter change | 2.06 US qt (1.95 L) |
| | After disassembly | 2.4 US qt (2.3 L) |
| Recommended brake (clutch) fluid | Honda DOT 4 Brake Fluid | |
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent | |
| Drive chain slack | 1 3/8 - 1 3/4 in (35 - 45 mm) | |
| Standard drive chain | RK 520MOZ6 or DID 520V8 | |
| | No. of links | 110 |
| Standard sprocket size | Engine sprocket | 15T |
| | Rear wheel sprocket | 45T |