

## Specifications

### Service Data

<b>CFT125MR/MS</b>	
Front	2.50-17 43L
Rear	2.50-17 43L
<b>CFT125MRC</b>	
Front	70/90-17M/C 38P
Rear	80/90-17M/C 50P
<b>CFT125MR/MS</b>	
Front	3.0 mm (0.12 in)
Rear	3.0 mm (0.12 in)
Bias-ply, tube	
Front	<b>CFT125MR/MS</b> MBP MM-102B
Rear	<b>CFT125MRC</b> MBP MP-220
Recommended Tyre	
Front	<b>CFT125MR/MS</b> MBP MM-102B
Rear	<b>CFT125MRC</b> MBP MP-221
[Rider only]	
Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	[Rider and 1 passenger]
	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
[Rider only]	
	225 kPa (2.25 kgf/cm <sup>2</sup> , 33 psi)
	[Rider and 1 passenger]
Rear	<b>CFT125MR/MS</b>
	280 kPa (2.80 kgf/cm <sup>2</sup> , 41 psi)
	<b>CFT125MRC</b>
	250 kPa (2.50 kgf/cm <sup>2</sup> , 36 psi)

Spark plug	(standard)	CPR7EA-9 (NGK) or U22EPR9 (DENSO)
Spark plug gap	0.8 - 0.9 mm (0.03 - 0.04 in)	
Idle speed	1,400 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	
Engine oil capacity		
	After draining	0.7 L (0.7 US qt, 0.6 Imp qt)
	After disassembly	0.9 L (1.0 US qt, 0.8 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	
Recommended drive chain lubricant	Drive chain lubricant If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	25 - 35 mm (1.0 - 1.4 in)	
Standard drive chain	DID420AD2 KMC420JB RK420EL	
	No. of links	104
Standard sprocket size	Drive sprocket	14 T
	Driven sprocket	38 T