## **Specifications**

## Main Components

Overall length	67.3 in (1,710 mm	)	
Overall width	29.7 in (755 mm)		
Overall height	40.6 in (1,030 mm)		
Wheelbase	45.5 in (1,155 mm)		
Minimum ground clearance	6.3 in (160 mm)		
Caster angle	25° 00′		
Trail	3.2 in (82 mm)		
Curb weight	Monkey125	231 lb (105 kg)	
	Monkey125A	236 lb (107 kg)	
Maximum weight capacity *1	229 lb (104 kg)		
Passenger capacity	Rider only		
Minimum turning radius	6.2 ft (1.9 m)		

\*1 : Including rider, all luggage, and accessories.

Displacement *1	7.6 cu-in (125 cm <sup>3</sup> )		
Bore x stroke	2.06 x 2.28 in (52.4 x 57.9 mm)		
Compression ratio	9.3 : 1		
Fuel	Unleaded gasoline		
	Recommended: 86 PON or higher		
Tank capacity	1.48 US gal (5.6 L)		
Battery	YTZ5S		
	12 V-3.5 Ah (10 HR)		
Gear ratio	1st	2.500	
	2nd	1.550	
	3rd	1.150	
	4th	0.923	
Reduction ratio (primary / final)	3.350 / 2.266		

\*1 : Displacement less than 9.2 cu-in (150 cm  $^3$ ) may have highway operating restrictions depending on state laws.