

## When the parts were revised



Be sure to check the serial number!!



| Ref. No. | Part No.        | Description  | Reqd. QTY |         | Serial No. |
|----------|-----------------|--|-----------|---------|------------|
|          |                 |  | CB400     | SFX SFY |            |
| 1        | 45156-MCE-000   | CLAMPER, R. FR. BRAKE HOSE                         | 1         | 1       |            |
| 2        | 45157-MCE-000   | CLAMPER, L. FR. BRAKE HOSE                         | 1         | 1       |            |
| 3        | 61100-MCE-000ZA | FENDER COMP., FR.<br>*NH411M*FORCE SILVER METALLIC | 1         | 1       | 31,4J      |
| 4        | 61100-MCE-000ZB | *PB284C*...CANDY PHOENIX BLUE                      | 1         | 1       | J,2J       |
| 6        | 61101-MCE-000   | PLATE, FR. FENDER (###)                            | 2         | 2       | 1008000    |
| 5        | 61101-MCE-010   | .....  | 2         | 2       | 1008000    |
| 5        | 61102-MCE-300   | CUSHION, FR. FENDER (BLACK)                        | 2         | 2       | 1008000    |
| 6        | 61105-MCE-000   | STAY, FR. FENDER MOUNTING                          | 2         | 2       |            |
| 7        | 61107-M67-000   | COLLAR (6.5)                                       | 4         | 4       |            |
| 8        | 96001-06020-00  | BOLT, FLANGE, 6X20                                 | 4         | 4       |            |

The number has been used from the initial model without revision.

When shown at the left side, it is applicable to the models of No.1008001 and the up to No.1008000.


When shown at the right side, it is applicable to the models of No.1008001 and the up to No.1008000.

The parts listed with "###" at the end of the parts name have limited supply period (parts not for sale).

## Abbreviations used in the parts catalogue



RIGHT is abbreviated as "R."



"L." stands for LEFT

\* "L." or "R." in the description of a part stands for the LEFT hand side or the RIGHT hand side. Determine the left or right as if you were in the motorcycle seat.

• The following abbreviations are used in this parts catalogue.

|        |       |                               |          |       |                         |
|--------|-------|-------------------------------|----------|-------|-------------------------|
| A      | ..... | Ampere                        | L        | ..... | Left                    |
| ABS    | ..... | Anti-lock brake system        | L (100L) | ..... | Link (100 Links)        |
| A.C.   | ..... | Alternating current           | L.E.D.   | ..... | Light emitted diode     |
| A.M.   | ..... | Attaching mark                | MM       | ..... | Millimeter              |
| ASSY.  | ..... | Assembly                      | MPH      | ..... | Miles per hour          |
| C.D.I. | ..... | Capacitive discharge ignition | R        | ..... | Right                   |
| COMP.  | ..... | Complete                      | RR       | ..... | Rear                    |
| CP.    | ..... | Candle power                  | STD.     | ..... | Standard                |
| D.C.   | ..... | Direct current                | T (22T)  | ..... | Tooth (22 Teeth)        |
| EX.    | ..... | Exhaust                       | TCS      | ..... | Traction control system |
| FR.    | ..... | Front                         | T.M.     | ..... | Transcript mark         |
| G      | ..... | Gram                          | V        | ..... | Volt                    |
| HEX.   | ..... | Hexagonal                     | W        | ..... | Watt                    |
| IN.    | ..... | Inlet                         | WL       | ..... | With labelling          |
| KPH    | ..... | Kilometers per hour           | WOL      | ..... | Without labelling       |