

Unit: mm (in)

Wheels/Tires		Standard	Service Limit
Item			
Minimum tire tread depth (FR)		_____	1.5 (0.06)
	(RR)	_____	2.0 (0.08)
Cold tire pressure	Driver only (FR)	250 kPa (2.5 kg/cm ² , 36 psi)	_____
	Driver only (RR)	290 kPa (2.9 kg/cm ² , 42 psi)	_____
	Driver and passenger (FR)	250 kPa (2.5 kg/cm ² , 36 psi)	_____
	Driver and passenger (RR)	290 kPa (2.9 kg/cm ² , 42 psi)	_____
Front and rear axle runout		_____	0.2 (0.01)
Front and rear wheel rim runout	(Radial)	_____	2.0 (0.08)
	(Axial)	_____	2.0 (0.08)
Wheel balance weight	(Front)	_____	60 g (2.1 oz)
	(Rear)	_____	60 g (2.1 oz)
Drive chain slack		15–25 (0.6–1.0)	_____
Drive chain size/link	(DID)	DID50ZV/114	_____
	(RK)	RK50LFO/114	_____

Front Suspension		
Fork spring free length	446.3 (17.57)	437.4 (17.22)
Fork spring direction	Tapered wound coil facing down	_____
Fork tube runout	_____	0.2 (0.01)
Recommended fork oil	Fork fluid	_____
Fork oil level	173 (6.8)	_____
Fork oil capacity	418 cm ³ (14.1 US oz, 11.8 Imp oz)	_____
Steering bearing preload	1.1–1.6 kg (2.43–3.53 lb)	_____

Rear Suspension		
Damper compressed gas	Nitrogen	_____
Damper drilling point	13 (0.5)	_____
		