

TORQUE VALUES

Brake hose oil bolt	34 N·m (3.5 kgf·m, 25 lbf·ft)
Rear brake caliper pad pin	18 N·m (1.8 kgf·m, 13 lbf·ft)
Rear caliper bleed valve	5.9 N·m (0.6 kgf·m, 4.3 lbf·ft)
Rear brake caliper slide pin bolt	27 N·m (2.8 kgf·m, 20 lbf·ft)
Rear brake caliper mounting bolt	23 N·m (2.3 kgf·m, 17 lbf·ft)
Rear brake hose clamp bolt	3.9 N·m (0.4 kgf·m, 2.9 lbf·ft)
Rear master cylinder push rod joint nut	18 N·m (1.8 kgf·m, 13 lbf·ft)
Rear brake reservoir hose joint screw	1.5 N·m (0.15 kgf·m, 1.1 lbf·ft)
Rear master cylinder reservoir cap screw	1.5 N·m (0.15 kgf·m, 1.1 lbf·ft)
Rear master cylinder reservoir mounting bolt	12 N·m (1.2 kgf·m, 9 lbf·ft)
Rear master cylinder mounting bolt	9.8 N·m (1.0 kgf·m, 7 lbf·ft)
Brake pedal pivot bolt	18 N·m (1.8 kgf·m, 13 lbf·ft)
Front brake caliper mounting bolt	45 N·m (4.6 kgf·m, 33 lbf·ft)
Front brake caliper assembly bolt	23 N·m (2.3 kgf·m, 17 lbf·ft)
Front brake caliper pad pin	16 N·m (1.6 kgf·m, 12 lbf·ft)
Front caliper bleed valve	7.8 N·m (0.8 kgf·m, 5.8 lbf·ft)
Front brake hose clamp	8.8 N·m (0.9 kgf·m, 6.5 lbf·ft)
Front brake hose 3-way joint bolt	9.8 N·m (1.0 kgf·m, 7 lbf·ft)
Front brake hose clamp (left side)	9.8 N·m (1.0 kgf·m, 7 lbf·ft)
Front master cylinder reservoir cap screw	1.5 N·m (0.15 kgf·m, 1.1 lbf·ft)
Front master cylinder reservoir stay bolt	12 N·m (1.2 kgf·m, 9 lbf·ft)
Front brake light switch screw	1.0 N·m (0.1 kgf·m, 0.7 lbf·ft)
Front master cylinder reservoir mounting nut	5.9 N·m (0.6 kgf·m, 4.3 lbf·ft)
Front brake lever pivot bolt	1.0 N·m (0.1 kgf·m, 0.7 lbf·ft)
Front brake lever pivot nut	5.9 N·m (0.6 kgf·m, 4.3 lbf·ft)
Front master cylinder bleed valve	5.9 N·m (0.6 kgf·m, 4.3 lbf·ft)
Front master cylinder holder bolt	12 N·m (1.2 kgf·m, 9 lbf·ft)

Apply a locking agent to the threads

ALOC bolt: replace with a new one
Apply a locking agent to the threads

U-nut

TOOLS

Snap ring pliers
07914-SA50001

