

# GENERAL INFORMATION

FRONT WHEEL/SUSPENSION/STEERING		Unit: mm (in)	
ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		_____	1.5 (0.06)
Cold tire pressure	Drive only	290 kPa (2.90 kgf/cm <sup>2</sup> , 42 psi)	_____
	Driver and passenger	290 kPa (2.90 kgf/cm <sup>2</sup> , 42 psi)	_____
Axle runout		_____	0.20 (0.008)
Wheel rim runout	Radial	_____	2.0 (0.08)
	Axial	_____	2.0 (0.08)
Fork	Spring free length	232.9 (9.17)	228.2 (8.98)
	Spring direction	With the tapered end facing down	_____
	Tube runout	_____	0.20 (0.008)
	Recommended fork fluid	Fork fluid	_____
	Fluid level	142 (5.6)	_____
Fluid capacity		483 ± 2.5 cm <sup>3</sup> (16.3 ± 0.08 US oz, 17.0 ± 0.09 Imp oz)	_____
Steering head bearing pre-load		10 – 15 N (1.0 – 1.5 kgf)	_____

REAR WHEEL/SUSPENSION			Unit: mm (in)	
ITEM			STANDARD	SERVICE LIMIT
Minimum tire tread depth			_____	2.0 (0.08)
Cold tire pressure	Driver only		290 kPa (2.90 kgf/cm <sup>2</sup> , 42 psi)	_____
	Driver and passenger		290 kPa (2.90 kgf/cm <sup>2</sup> , 42 psi)	_____
Axle runout			_____	0.20 (0.008)
Wheel rim runout	Radial		_____	2.0 (0.08)
	Axial		_____	2.0 (0.08)
Drive chain	Size/link	DID	DID50ZVS-110LE	_____
		RK	RK50LFOZ1-110LE	_____
	Slack		25 – 35 (1.0 – 1.4)	50 (2.0)
Shock absorber	Spring installed length		209.1 (8.23)	_____